

VESPA PRIMAVERA TECH 50 – TECHNICAL SPECIFICATIONS

ENGINE Single cylinder 4-stroke, 3 valves, i-get **ENGINE CAPACITY** 49 cc BORE X STROKE 39 mm x 41.4 mm MAX POWER AT 2.3 kW - 3.1 HP - at 7,750 rpm THE CRANK SHAFT MAX TORQUE 3.1 Nm at 5,750 rpm CONSUMPTION 38,5 km/l CO2 EMISSIONS 59 g/km COMPLIANCE FUEL SYSTEM Electronic injection **COOLING** Forced air **STARTER** Electric **GEARBOX** CVT continuously variable transmission with torque server **CLUTCH** Automatic centrifugal dry clutch with vibration dampers LOAD-BEARING Sheet steel body with welded reinforcements **STRUCTURE FRONT** Single-sided link arm with coil spring and hydraulic monoshock **SUSPENSION** absorber REAR Coil spring with hydraulic monoshock absorber **SUSPENSION** FRONT BRAKE Ø 200 mm stainless steel disc with hydraulic control **REAR BRAKE** Ø 140 mm drum mechanically operated ABS SYSTEM -FRONT TYRE Tubeless 110/70 - 12" REAR TYRE Tubeless 120/70 - 12" LENGTH / 1,860 / 745 / 1,330 mm WIDTH / WHEELBASE SEAT HEIGHT 785 mm FUEL TANK CAPACITY 7.5 litres EMISSIONS COMPLIANCE Euro 5