



SPRINT S 50 – TECHNICAL SPECIFICATIONS

ENGINE	Single cylinder 4-stroke, 3 valves, i-get
DISPLACEMENT	49 cc
BORE X STROKE	39 mm x 41,8 mm
MAX POWER AT THE CRANK SHAFT	-
MAX TORQUE	-
CONSUMPTION	-
CO2 EMISSIONS COMPLIANCE	-
FUEL SYSTEM	Electronic injection
COOLING	Forced air
STARTER	Electric
GEARBOX	CVT continuously variable transmission with torque server
CLUTCH	Automatic centrifugal dry clutch with vibration dampers
LOAD-BEARING STRUCTURE	Sheet steel body with welded reinforcements
FRONT SUSPENSION	Single-sided link arm with coil spring and hydraulic monoshock absorber
REAR SUSPENSION	Coil spring with hydraulic monoshock absorber
FRONT BRAKE	Ø 200 mm stainless steel disc with hydraulic control
REAR BRAKE	Ø 140 mm drum mechanically operated
ABS SYSTEM	-
FRONT TYRE	Tubeless 110/70 - 12"
REAR TYRE	Tubeless 120/70 - 12"
LENGTH / WIDTH / WHEELBASE	-
SEAT HEIGHT	790 mm
FUEL TANK CAPACITY	7,5 litres
EMISSIONS COMPLIANCE	Euro 5